

DATENBLATT

LED IN MOTION MODEL „P2“

Pixel Pitch	2mm
Destiny	250,000 dots/SQM
LED Type	SMD1515 Mat Black
Pixel Type(R/G/B)	1R1G1B (3 in 1)
Module Size	256 x128 mm
Module Resolution	128*64 Pixel
Screen Size (H*W)	768*1920 mm
Feet Size	2,52 * 6,3 feet
Screen Resolution	384*960 pixel
Frame Size	1930mm (H) * 776mm (W) * 45mm (T)
Case Material	Aluminium
Weight	46kg / unit
Drive Mode	1/32 Scan
Viewing Distance	≥ 2m
Brightness	≥ 1,000 cd/m ²
Viewing Angle	140° (H) / 140° (V)
Refresh Rate	≥ 1,920 Hz (3840HZ optional)
Input Voltage	AC90-240V
Maximum Power Consumption	1170W per unit
Average Power Consumption	350W per unit
Control Method	Asynchronous (WIFI/USB/LAN/HDMI)
Temperature Operating (°C)	-40°~+75°
Working Humidity	10% - 95% RH
IP Rating	IP20
Application	Indoor/ Semi-Outdoor
Certificate	CE/ROHS/FCC

DATENBLATT

LED IN MOTION MODEL „P2.5“

Pixel Pitch	2,5mm
Destiny	160,000 dots/SQM
LED Type	SMD2121 Mat Black
Pixel Type(R/G/B)	1R1G1B (3 in 1)
Module Size	160x160 mm
Module Resolution	64*64 Pixel
Screen Size (H*W)	640*1920 mm
Feet Size	2,10 * 6,3 feet
Screen Resolution	256*768 pixel
Frame Size	1930mm (H) * 648mm (W) * 45mm (T)
Case Material	Aluminium
Weight	38kg / unit
Drive Mode	1/32 Scan
Viewing Distance	≥ 2,5m
Brightness	≥ 1,000 cd/m ²
Viewing Angle	140° (H) / 140° (V)
Refresh Rate	≥ 1,920 Hz (3840HZ optional)
Input Voltage	AC90-240V
Maximum Power Consumption	750W per unit
Average Power Consumption	220W per unit
Control Method	Asynchronous (WIFI/USB/LAN/HDMI)
Temperature Operating (°C)	-40°~+75°
Working Humidity	10% - 95% RH
IP Rating	IP20
Application	Indoor/ Semi-Outdoor
Certificate	CE/ROHS/FCC

DATENBLATT

LED IN MOTION MODEL „P3“

Pixel Pitch	3mm
Destiny	111,111 dots/SQM
LED Type	SMD2121 Mat Black
Pixel Type(R/G/B)	1R1G1B (3 in 1)
Module Size	192 x 192 mm
Module Resolution	64*64 Pixel
Screen Size (H*W)	576*1920 mm
Feet Size	1,88 * 6,3 feet
Screen Resolution	192*640 pixel
Frame Size	1930mm (H) * 584mm (W) * 45mm (T)
Case Material	Aluminium
Weight	35kg / unit
Drive Mode	1/16 Scan
Viewing Distance	≥ 3m
Brightness	≥ 1,000 cd/m2
Viewing Angle	140° (H) / 140° (V)
Refresh Rate	≥ 1,920 Hz (3840HZ optional)
Input Voltage	AC90-240V
Maximum Power Consumption	600W per unit
Average Power Consumption	280W per unit
Control Method	Asynchronous (WIFI/USB/LAN/HDMI)
Temperature Operating (°C)	-40°~+75°
Working Humidity	10% - 95% RH
IP Rating	IP20
Application	Indoor/ Semi-Outdoor
Certificate	CE/ROHS/FCC

PREISE

INDOOR

MODEL	1 MODUL	3 MODULE	5 MODULE	6 MODULE
P3	4.550	11.925 (3.975 / Stk.)	-	20.940 (3.490 / Stk.)
P2.5	5.500	14.520 (4.840 / Stk.)	22.300 (4.460 / Stk.)	25.860 (4.310 / Stk.)
P2	6.850	18.960 (6.320 / Stk.)	27.600 (6.320 / Stk.)	31.950 (5.325 / Stk.)

OUTDOOR

MODEL	1 MODUL	3 MODULE	5 MODULE	6 MODULE
P3	6.250	16.950 (5.650 / Stk.)	-	31.500 (5.250 / Stk.)
P2.5	7.150	19.950 (6.650 / Stk.)	29.750 (5.950 / Stk.)	34.500 (5.750 / Stk.)